



# RAPTOR<sup>®</sup> SD

## MORE FEATURES, MORE MUSCLE - MAKES SMALL WORK OUT OF BIG JOBS

Ideal For Yards Up To Three Acres

#### HIGHLIGHTS

- 36", 42", 48", 54" or 60" welded-steel deck
- Heavy-duty fabricated frame unmatched durability
- Exclusive SmoothTrak™ steering responsive, precise control



**ENGINE** Manufacturer Kohler 7000 Series HD or 7000 Series PRO (both with Smart-Choke<sup>™</sup>) 36", 42" deck: 22HP\* - 7000 HD 48", 54" deck: 25HP\* - 7000 PRO 60"deck: 26HP\* - 7000 PRO \* Per SAE J 1995 36", 42", 48", 54" deck: 725cc Displacement 60" deck: 747cc Cooling Air cooled **Engine Warranty** 3 year **DRIVE SYSTEM** Type Dual hydrostatic Transmission Hydro-Gear ZT-2800 Speed 7.5 mph Parking Brakes Patented automatic **DECKS Cutting Width** Side discharge: 36", 42", 48", 54", 60" **Cutting Heights** 1.5"- 4.5" Deck Lift Foot operated Depth 4.5" 36"deck: 2 42"deck: 2 Blades 48"deck: 3 54"deck: 3 60"deck: 3 Blade Length 36"deck: 2 - 17.86" x 2.50" x .20" 42"deck: 2 - 20.50" x 2.50" x .20" 48"deck: 3 - 16.50" x 2.50" x .20" 54"deck: 3 - 18.50" x 2.50" x .20" 60"deck: 3 - 20.50" x 2.50" x .20" Spindles Aluminum w/ 1.0" shafts and double lip sealed ball bearings Drive Electric PTO clutch Construction 11 ga. fabricated Spindle Mounts Reinforced 7 ga. Impact/Trim Areas 3/8" x 1" steel bar

Front Caster Wheels Commercial duty steel roller bearings, greasable Front Caster Forks Fabricated 3/8" steel **GENERAL** 36", 42", 48", 54": Premium seat with armrests 60": Adjustable premium bolstered seat with armrests. Internal suspension. **Fuel Capacity** 3 gallons Cup Holder 36", 42", 48": 13 x 5 - 6 Front Tire 54", 60": 13 x 6.5 - 6 36", 42": 20 x 6.5 - 10 Drive Tire 48": 20 x 8 - 10 54", 60": 20 x 12 - 10 **DIMENSIONS** Weight 36": 586 lbs 54": 666 lbs 42": 590 lbs 60": 671 lbs 48": 638 lbs Height 36", 42", 48", 54": 42" 60": 44"

#### PRODUCTIVITY\*

Length

Width

Tire Width

Acres Per Hour 36": 2.18 54": 3.27 42": 2.54 60": 3.64

73"

36": 37.3"

42": 44.4"

36", 42": 38.3"

48": 49"

48": 41"

48": 2.91

OPTIONAL Mulch kit
ACCESSORIES Grass cate

Grass catcher (non-powered 5.4 bushels)

Lights FlexForks

Steering extension kit

Engine guard

Stripe kit (48", 54", 60" decks only)

54": 55"

60": 61"

54": 46"

60": 46"

\* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

### CONSTRUCTION

Frame 3.25" x 1.5" x .120" steel

Front Axle Fabricated with sealed ball bearings

