



LIMITED WARRANTY
2 YEAR | **NO** HOUR LIMIT

OR

LIMITED WARRANTY
5 YEAR | **500** HOUR

SUPER S[®]

STAND-ON WITH EXCEPTIONAL COMPACT STANCE FOR TIGHT SPACES AND TRAILERING

HIGHLIGHTS

- 36", 48", 52" or 60" side-discharge deck
- Heavy-duty fabricated frame – unmatched durability
- Exclusive SmoothTrak™ steering – responsive, precise control
- Patented automatic parking brake
- Compact stance – great for tight spaces
- Superior operator comfort and positioning
- Operator-friendly ergonomic controls



ENGINE	
Manufacturer	Kawasaki FS541V, FX691V, FX730V Kohler ECV730 EFI, ECV740 EFI
HP	36"deck: 15HP* - FS541V 48/52"deck: 22HP* - FX691V 60"deck: 23.5HP* - FX730V 52"deck: 23HP* - ECV730 EFI 60"deck: 25HP* - ECV740 EFI * Per SAE J 1995
Displacement	603-747cc
Cooling	Air cooled
Air Cleaner	Heavy duty air canister (not standard on 36" deck)
Engine Warranty	3 year
DRIVE SYSTEM	
Type	Dual hydrostatic
Pumps	36": Hydro-Gear 10cc 48, 52, 60": Hydro-Gear 12cc
Wheel Motors	36": Parker TL0195 48, 52, 60": Parker TL0240
Speed	36": 8 mph 48, 52, 60": 9 mph
Parking Brakes	Hand operated
DECKS	
Cutting Width	Side discharge: 36", 48", 52", 60"
Cutting Heights	1.5"- 5.5"
Deck Lift	Hand operated
Depth	5.5"
Blades	36": 2 48", 52", 60": 3
Blade Length	36" deck: 17.86" x 2.50" x .20" 48" deck: 16.50" x 2.50" x .20" 52" deck: 17.86" x 2.50" x .20" 60" deck: 20.50" x 2.50" x .20"
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Deck Belts	1
Drive	Electric PTO clutch
Construction	36": 7 ga. Fabricated 48, 52, 60": 10 ga. Fabricated
Spindle Mounts	36": 7 ga. with 11 ga. doubler 48, 52, 60": 10 ga. with 7 ga. doubler
Impact/Trim Areas	11 ga. formed channel with rolled bottom

CONSTRUCTION	
Frame	36": 1.5" x 2" x .179" steel 48, 52, 60": 1.5" x 3" x .188" steel
Engine Plate	7 ga. with 11 ga. jackshaft doubler
Front Caster Wheels	Heavy duty ball bearing, greasable
Front Caster Forks	Fabricated 3/8" steel
Operator Platform	7 ga. with embossed tread pattern
GENERAL	
Fuel Capacity	36": 6.5 gallons 48, 52, 60": 7.3 gallons
Front Tire	36": 11 x 4 semi pneumatic 48", 52", 60": 13 x 5 semi pneumatic
Drive Tire	36": 18 x 8.5 - 10 48", 52": 20 x 10 - 10 60": 20 x 12 - 10
DIMENSIONS	
Weight	36": 910 lbs 48": 1040 lbs 52": 1055 lbs 60": 1110 lbs
Height	47.8"
Length	36": 63.5" 48", 52": 64" 60": 66.5"
Width w/ chute up	36": 39" 48": 50.4" 52": 54.4" 60": 62.4"
Tire Width	36": 36.3" 48", 52": 44.7" 60": 49.1"
PRODUCTIVITY*	
Acres Per Hour	36": 2.33 48": 3.49 52": 3.93 60": 4.36
OPTIONAL ACCESSORIES	
	Mulch kit Grass catcher (4.4 cu.ft.) Light kit Cup holder Trash basket Stripe kit

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.